

PRODUCT SPECIFICATIONS 1 OF 1

PRODUCT DESCRIPTION



Aztec Plumbing PTFE Thread Seal Tape is a white tape made from Polytetrafluoroethylene (PTFE) that provides tight seal and permits easy disassembly. It is flame resistant and white color coded for easy identification. It is compatible with a broad range of piping materials and is chemical inert and withstands solvents from a temperature range from -450° F to +500° F. PTFE thread Seal Tape is non-toxic.

Meets Federal Specification MIL-T-27730A.

INGREDIENTS (CAS number)

Polytetrafluoroethylene,
PTFE (CAS. 9002-84-0)

PHYSICAL AND CHEMICAL PROPERTIES

Solubility in water	Insoluble
Thickness, mm	0.089 (+/- 0.05)
Width, mm	12.0 (+/- 0.05)
Elongation (%)	50.0 Min
Volatile Loss (%)	10 Max

DIRECTIONS FOR USE

- Apply in a clean and dry surface.
- Apply the PTFE Thread Seal Tape to male threads as close as possible to the end of the threads, while stretching the tape tightly.
- Assemble joints in usual manner.

PRECAUTIONS

If swallowed, seek immediate medical attention. **KEEP OUT OF REACH OF CHILDREN.**

For more information visit our website at www.aztec-plumbing.com or contact your sales representative.

Aztec Plumbing PTFE Thread Seal Tape – rev. 05-11-2015