

PRODUCT SPECIFICATIONS 1 OF 1



PRODUCT DESCRIPTION

Aztec Plumbing Pipe Joint Compound with PTFE is formulated to form a film of PTFE in threads connections, to lubricate and seal, providing long protection against leaks. It is water and gas proof and will not harden, shrink, crack or crumble. It could work at temperatures between -50° to +400°F and it can be applied to any metal, PVC, CPVC, ABS, polypropylene and nylon.

Meets Federal Specification TT-S-1732.

INGREDIENTS (CAS number)

Polytetrafluoroethylene,
PTFE (CAS. 9002-84-0)
Ethylene Glycol N-Butyl Ether
(CAS.111-76-2)
Vegetable Oil (CAS. 8001-22-7)
Calcium carbonate (CAS. 471-34-1)

PHYSICAL AND CHEMICAL PROPERTIES

Specific gravity	1.41
Shelf life	1 year from manufacture date
Solubility in water	Insoluble
Odor	Mild petroleum
Appearance	White paste

DIRECTIONS FOR USE

- Apply in a clean and dry surface.
- Brush well the threads before applying the product.
- Do not dilute.
- Apply the compound to male threads with the brush or applicator.
- Assemble in usual manner.

PRECAUTIONS

Avoid contact with eyes; wash with abundant water after handling. If swallowed, seek immediate medical attention. **KEEP OUT OF REACH OF CHILDREN.**