

## PRODUCT SPECIFICATIONS 1 OF 1

---



### PRODUCT DESCRIPTION

Aztec Plumbing Valve Grease is a blend of lithium soaps, refined base stocks and extreme pressure additives, to be used in many plumbers' applications. With an operation temperature up to 275°F, lubricating stems of faucets, valves, ballcocks etc. Not for use on rubber or synthetic O-Rings.

### INGREDIENTS (CAS number)

12-Hydroxy Stearic Acid  
(CAS.106-14-9)  
Lithium Carbonate  
(CAS.554-13-2)  
Distillates (petroleum)  
(CAS. 64742-65-0)  
Antirust and Antioxidant Additive  
(CAS. 471-34-1)

### DIRECTIONS FOR USE

- Clean and dry the surface.
- Apply by hand or brush.

### PHYSICAL AND CHEMICAL PROPERTIES

	<b>ASTM Method</b>	<b>Spec</b>
Loss of Mechanical Stability, %	D 217	10 Max.
Oxidation Stability, 100 hrs., psi.	D 942	15 Max.
Water Washout @ 176°F, %.	D 1264	5 Max.
Corrosion Preventive Properties	D 1743	Pass

### PRECAUTIONS

Avoid contact with eyes; wash with abundant water after handling. If swallowed, seek immediate medical attention. **KEEP OUT OF REACH OF CHILDREN.**