



**PRODUCT DESCRIPTION**

Aztec Plumbing's Plumbers putty is formulated to make a perfect watertight seal around faucets and drains. It remains soft and flexible; it is water and gas proof and will not harden, shrink, crack or crumble.

Meets Federal Specification TT-P-1536A.

**INGREDIENTS (CAS number)**

Hydrocarbon Oil (CAS. 64742-52-5)  
Vegetable Oil (CAS.120962-03-0)  
Calcium Carbonate (CAS. 471-34-1)

**PHYSICAL AND CHEMICAL PROPERTIES**

Specific gravity	2.10
Shelf life	1 year from manufacture date
Solubility in water	Insoluble
Odor	Mild petroleum
Appearance	Beige Putty

**DIRECTIONS FOR USE**

- Apply in a clean and dry surface.
- Knead putty in hands and form a cord like shape.
- Place the putty on the surface to be sealed.
- The excess of the putty should squeeze out and be removed with a putty knife.
- For natural stone marble surface, apply a coat of clear acrylic lacquer; allow drying and then apply the Plumber's Putty as noted above.

**PRECAUTIONS**

Avoid contact with eyes; wash with abundant water after handling. If swallowed, seek immediate medical attention. DO NOT USE PLUMBERS PUTTY ON MARBLE, GRANITE, OR ANY OTHER POUROS STONE. DO NOT USE IN PLASTIC. KEEP OUT OF REACH OF CHILDREN.

DESCRIPTION	PACK	CARTON WEIGHT
14 oz. Plumber's Putty	24	23.2 lb.
3 lb. Plumber's Putty	6	20.2 lb.
5 lb. Plumber's Putty	6	32.2 lb.

For more information visit our website at [www.aztec-plumbing.com](http://www.aztec-plumbing.com) or contact your sales representative.